

A wide measurement range of particle from 0.2 μm to 2.0 μm .
Measurements can be made using only small amounts of
samples due to high counting efficiency.



Liquid-Borne Particle Sensor KS-42B/42BF [Compatible with Hydrofluoric acid]


- Detects particles down to 0.2 μm size,
at a flow rate of 10 mL/min
- Five particle size ranges (5 channels, factory default setting)
 $\geq 0.2 \mu\text{m}$, $\geq 0.3 \mu\text{m}$, $\geq 0.5 \mu\text{m}$, $\geq 1.0 \mu\text{m}$, $\geq 2.0 \mu\text{m}$
- Integrated leak sensor with alarm output
- A sapphire flow cell is used in KS-42BF
- User selectable channels within measurement range
(using KE-40B1 function)



Specifications [KS-42B/42BF]

Optical system	Light-scattering method
Light source	Laser diode (wavelength 780 nm, rated output 40 mW)
Laser product class	Class 1, IEC 60825-1
Light detector	PIN type photodiode
Materials of parts exposed to sample	KS-42B: Synthetic quartz, PFA, PTFE KS-42BF: Sapphire, PFA, PTFE
Allowable sample type	Any liquid that does not corrode contacting materials
Calibration	Polystyrene latex (PSL) particles (refractive index 1.6) in pure water
Size range	
5 channels (factory default)	$\geq 0.2 \mu\text{m}$, $\geq 0.3 \mu\text{m}$, $\geq 0.5 \mu\text{m}$, $\geq 1.0 \mu\text{m}$, $\geq 2.0 \mu\text{m}$
User selectable channels	1 channel to 10 channels, setting made from Controller
Setting range	0.2 μm to 2.0 μm
Counting efficiency	KS-42B, KS-42BF: 70 % to 110 %
Flow rate	10 mL/min
Maximum particle number concentration	1 200 particles/mL (at 5 % coincidence loss for 0.2 μm particles)
Sample temperature range	+15 °C to +35 °C (no condensation in the cell part)
Sample pressure range	300 kPa (gauge pressure) or less
Sample inlet/outlet	2 (dia.) x 4 (dia.) flared joint for tube
Purge air port	Rc1/8 (1/8 PT female screw)
Input/output connector	
CONTROLLER connector	Connecting to KE-40B1
LIQUID LEAK ALARM connector	Alarm output terminal shorted during normal operation, open when internal leak is detected
Power	DC12 V (supplied by KE-40B1)
Environmental conditions for operation	+15 °C to +35 °C, less than 85 % RH (no condensation)
Dimensions and weight	125 (H) x 240 (W) x 151 (D) mm (excluding protrusions), Approx. 3.2 kg
Accessories	Tube A vacuum pack x 1 (2 x 4 dia. PFA tube with flared joint at one end, 1.5 m x 2, Union joint x 1), Connection cable (1 m) x 1
Options	Connection cable (5 m) KS-42-123

Example of measuring system




RP monitor K9461 Ver. 2

Option

Enables automatic control of particle counter, data collection, real-time graph display, filing and printout using a computer

- Enables data processing using spreadsheet software (Windows Excel, etc.)
- Enables one-to-one control of RION particle counters in the RS-232C mode

Compatible OS: Microsoft Windows 2000/XP



Sample display

Syringe Sampler KZ-30W1/30W2

For batch measurement of liquid-borne particle sensor

*Connecting cable (KZ30S180, optional)



For operation control of particle sensor and display of measurement data

Controller KE-40B1

- Particle size range can be freely set for up to 10 channels.
- Built-in printer.
Measurement data can be stored on memory card (CF card).



Specifications [KE-40B1]

Display	
Display items	Particle size range (max.10 channels), Count (max. 8 digits)
Controls	Touch panel, Sheet switches
Measurement	
Measurement time	10 seconds to 2 hours, or manual
Measurement modes	Manual measurement Automatic measurement: mean value measurement, moving average measurement, periodic measurement, scheduled time measurement
Alarm	When measured value in a selected channel reaches or exceeds the preset alarm level, a buzzer sounds and alarm terminals are shorted by relay contacts Maximum connected load: DC 30 V, 1 A
Communication	RS-232C
Printer	Printout of measurement results, date and time
Recording paper	Thermal paper: TP-08, Clean thermal paper: TP-10
Memory	CompactFlash (CF) card [®] (automatic storage in TSV format)
Power	100 to 240 V AC, 50/60 Hz, 130 VA
Dimensions and weight	140 (H) x 240 (W) x 150 (D) mm (excluding protruding parts), approx. 3 kg
Accessories	Power cord x 1, Thermal paper TP-08 x 2 rolls, Touch pen, Dummy card
Options	Communication cable CC-61A, Thermal paper TP-08, Clean thermal paper TP-10, Memory card(128 MB) MC-12CF1/(256 MB)MC-25CF1, CFcard adapter CFC-ADP03
Factory option	D/A converter interface KE-40-S06
*Use only RION supplied cards for assured operation.	

* Company names and product names mentioned in this catalog are usually trademarks or registered trademarks of their respective owners.
* Specifications subject to change without notice.



Distributed by:

RION CO., LTD.
<http://www.rion.co.jp/english/>

3-20-41, Higashimotomachi, Kokubunji,
Tokyo 185-8533, Japan
Tel: +81-423-59-7878, Fax: +81-423-59-7458